

GF6 Profi-Set Fiberglass rod Ø 6 mm

for pipe diameter 40 - 100 mm, incl. double run-out system

Item no.: **10059** | **10061** | **10063** | **10065**

VIDEO
GF6
Click here Video

KG 320

Click here Productinformation

Ergonomic holding and carrying handle

Lateral parking brake

RG7 - Guiding head with front thread and eyelet incl. swivel

Double run-out system, quick outlet and automatic run-out brake

Extendable standing feet and storage compartment incl. accessories

Beginning: RG7 - Guiding head with swivel Ø 7 mm, RTG Ø 6 mm thread, screwed to strand

Ending: Ending joint, stainless steel, thread RTG Ø 6 mm

Attention!
Electric conductive

Detailed image

Extendable feet

Lateral parking brake and double run-out system (quick outlet and automatic run-out brake)

Quick run with rollers Automatic run-out brake

Rod	rec. pipe diameter Ø	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
6 mm	40 - 100 mm	168 mm	80 mm	2200 kg	320 kg

DATA

ITEM NO.:	10059	10061	10063	10055
LENGTH	40 m	50 m	60 m	80 m
WEIGHT	7,29 kg	7,69 kg	8,10 kg	8,90 kg
MATERIAL ROD	Fiberglass core with PP sheath			
BENDING RADIUS	168 mm			
PIPE Ø	optimal for tube diameter 40 - 100 mm			
DIMENSION	L x 550 x B 270 x H 645 mm			
TOTAL BREAKING LOAD	320 kg			

DESCRIPTION

GF6 Fiberglass rod (duct rodders) Ø 6 mm Profi-Set - RTG Ø 6 mm thread with robust steel reel Ø 530 mm (CDP/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Fiberglass rod breaking load 2200 kg, total breaking load 320 kg.

Optimal field of application: for pipe diameters 40 mm - 100 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x GF6 Fiberglass rod Ø 6 mm Profi-Set, stainless steel ending joint on both sides (start/end), 1 x steel reel Ø 530 mm incl. double run-out system, extendable feet and storage compartment, additional accessories: 1 x RG7 RUNPOGLIDER with thread and swivel, 2 x ending joint, 1 x coupling joint, 1 x shackle, 1 x special glue, 1 x roller

ADVANTAGES

- incl. steel reel Ø 530 mm
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 2200 kg
- Total breaking load 320 kg
- Bending radius with ending joint 168 mm

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140
50 m - Item no.: 10141



Click here
Productinformation

RC3 Inspection camera (digital)

15 m - Item no. 10214



Click here
Productinformation