

GF7.5 Fiberglass rod Ø 7,5 mm

for pipe diameter 50 - 120 mm, incl. double run-out-system

Item. no. **10076** | **10077** | **10078** | **10079** | **10080** | **10091**

VIDEO

GF7.5

Click here Video

KG 400

Ø 7,5 mm

- Ergonomic holding and carrying handle
- Autom. run-out brake
- Lateral parking brake
- Meter counter with hardened thumb wheel
- Quick run with mounted rollers
- Mobile reel CDP / powder-coated
- 2 x threaded bolts (for roller or starting head)

Rod tip: Shackle, stainless steel, RTG Ø 12 mm thread, screwed to strang

Rod end: Ending joint, stainless steel, RTG Ø 12 mm thread

Double run-out-system
(Quick run and automatic run-out brake)

Quick run with mounted rollers

Automatic run-out brake rollers

Meter counter with hardened thumb wheel

Additional option: Adaptable leading heads

6-digit roller counter with meter and 10 cm steps

13-parts flexible leading head-set

Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
7,5 mm	50 - 120 mm	500 mm	115 mm	3400 kg	400 kg

DATA

ITEM. NO.	10076	10077	10078	10079	10080	10091
LENGTH	40 m	50 m	60 m	80 m	100 m	120 m
WEIGHT	18,17 kg	18,71 kg	19,33 kg	20,70 kg	21,00 kg	22,00 kg
MATERIAL ROD	Fiberglass core with PP sheath					
BENDING RADIUS	500 mm					
PIPE Ø	optimal from 50 - 120 mm					
DIMENSION	L 830 mm W 400 mm H 900 mm					
TOTAL BREAKING LOAD	400 kg					

DESCRIPTION

GF7.5 cable puller fiberglass rod (duct rodders) Ø 7.5 mm - Cable pulling tool - RUNPOTEC RTG Ø 12 mm thread with robust steel reel (CDP/powder coated) Ø 730 mm incl. new double run-out system (automatic run-out brake and fast run-out), additional parking brake. The shackle also has a transition thread to RTG Ø 6 mm to adapt various guide rods (RUNPOSTICKS), guide probes, cable pulling grip (sock), RC2 or RC3 inspection camera and the like. Fiberglass rod breaking load 3400 kg, total breaking load 400 kg.

Optimal field of application: for pipe diameters 50 mm - 120 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x GF7.5 Fiberglass rod Ø 7,5 mm, stainless steel ending joint (start/end) 1 x steel reel Ø 730 mm mobile incl. double run-out-system, 1 x meter counter, 1 x shackle

ADVANTAGES

- Incl. steel reel and meter counter
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 3400 kg
- Total breaking load 400 kg
- Bending radius only rod 115 mm
- Bending radius with ending joint 500 mm

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140

50 m - Item no.: 10141



Click here
Productinformation

RC3 Inspection camera (digital)

15 m - Item no. 10214

Click here
Productinformation

