

POLYESTER CABLE PULLING ROPE incl. steel reel

Rope Ø 12 mm for CW 800 E capstan winch

Item no.: **10120** | **10121** | **10122** | **10123**

VIDEO

CW 800 E

[Click here Video](#)

KG
2180

[Click here Productinformation](#)

Detail images

DATA

ITEM NO.	10120	10121	10122	10123
ROPE Ø	Ø 12 mm	Ø 12 mm	Ø 12 mm	Ø 12 mm
ROPE LENGTH	150 m	200 m	300 m	350 m
REEL BASKET Ø	770 mm	770 mm	770 mm	770 mm
INTERNAL REEL BASKET	98 mm	98 mm	192 mm	192 mm
DIMENSION MM	L 815 W 280 H 900	L 830 W 390 H 900	L 830 W 500 H 900	L 830 W 500 H 900
TOTAL WEIGHT	31,5 kg	36 kg	51 kg	52 kg
TOTAL BREAKING LOAD	2180 kg			
MATERIAL ROPE	Polyester - Rope			
LOOP	2x spliced-in loops			
EAN-CODE	9120045475364	9120045475371	9120045475388	9120045475395

ADVANTAGES

- Spliced loops at the start and end of the rope
- Low rope elongation
- Practical reel for controlled winding and unwinding of the rope
- Reel Ø 770 mm mobile with wheel
- Reel with parking brake

DESCRIPTION

RUNPOTEC polyester pulling ropes are optimally suited for horizontal cable pulling with the RUNPOTEC CW 800 E capstan winch. RUNPOTEC recommends using the connecting swirl with swivel for horizontal cable pulling. It reduces frictional resistance and protects the cable and the feed system. The reel allows controlled winding and unwinding of the rope. In addition, the rope is perfectly stowed away and ready for use at any time. The 770 mm reel cage size can be easily rolled and transported due to the integrated wheels. The reel is CDP/powder coated.

Safety instructions: Not suitable for vertical cable pulling, must not be used to carry or lift loads or persons.

Optimal application: for horizontal cable pulling in combination with the CW 800 E capstan winch.

Scope of delivery: 1 x Polyester cable pulling rope Ø 12 mm incl. steel reel

INFORMATION**Accessories:****Connection swirl**

incl. swivel
Item no. 10176



[Click here Productinformation](#)

Related Pullingsystem:**CW 800 E Capstan winch + Trolley**

Item no. 10138



[Click here Productinformation](#)