

RC2 Inspection camera

for pipe inspection – in lengths of 10 m, 30 m and 50 m

Item no.: **10139** | **10140** | **10141**

Extensive accessories included



DATA

ITEM NO.:	10140	10141
CABLE LENGTH M	30 m	50 m
TOTAL WEIGHT KG	3,52 kg	4,08 kg
EAN-CODE	9120045475562	9120045475579
CASE SIZE MM	L 437 mm x W 405 mm x H 137 mm	
MONITOR	3,5" TFT LCD Monitor 16 M color	
CAMERA PROBE	307.200 Pixel (640 x 480)	
ILLUMINATION	6 x LED (integrated in camera probe)	
PROTECTION CLASS	IP 67 (camera probe and cable)	
FIELD OF VIEW	64 °	
FOCUSSING DISTANCE	30 mm – 80 mm	
POWER SUPPLY	230 V or battery-operated (battery included)	
LANGUAGES	DE, EN, FR, ES, PT, IT, NL, DK, SE, NO, FI, PL, CZ, HU, RU, IS, LT, SK, SL, HR, TR, BGR	

DESCRIPTION

The RC2 inspection camera (analogue) with coil incl. monitor holder is the perfect solution for precise pipe and cavity inspections at distances of up to 50 meters. With 6 integrated LEDs and an extra-large 3.5" TFT LCD color display, it delivers razor-sharp images and videos, ideal for preserving evidence through photo, video and audio recordings. The robust stainless steel camera head (Ø 13 mm) with RTG Ø 6 mm internal thread is compatible with all RUNPOTEC products with RTG Ø 6 mm thread, including GF3, RUNPOSTICKS, RP 1 and fiberglass rods GF4.5 - GF15. Thanks to the IP67 protection class (camera head and cable), the camera is dust and water resistant, and the battery lasts up to 6 hours for uninterrupted work. Note: The RC2 inspection camera can only be used with RUNPOTEC slide-in systems. **Optimal area of application:** The camera is ideal for pipe inspections up to 50 m in length, from an internal diameter of 14 mm (corresponds to empty pipe Ø 20 mm) and is ideal for larger pipe cross-sections (ventilation systems, drains, sewage pipes, etc.). In combination with the RUNPOSTICKS, it also enables cavity wall inspections, inspections of suspended ceilings (via high ceiling profiles), shafts and underfloor ducts, maintenance and system inspections

Scope of supply: 1 x RC2 inspection camera – incl. extensive accessories, (Scope of supply see on the top of the page)

ADVANTAGES

- Protection class IP67 (camera probe)
- Pipe inspection from Inner-Ø 14 mm
- Ventilation pipes, drainage pipes, sewage pipes and much more
- Also for cavity inspection and suspended ceilings
- In lengths of 30 m and 50 m
- RC2 inspection camera in robust stainless steel head with cable on reel
- Memory function/documented evidence Photo (JPG), Video (AVI)
- Spool with camera cable can be easily unwound or wound using the XB Cable roller series.

INFORMATION

Use with:

RP1 Cable pulling rod Ø 4 mm

Lengths: 5 - 30 m

Item no.: 30027 - 30030 m

Item no.: 30042 - 30043 m

GF3 Fiberglass rod Ø 3 mm

Item no.: 10192 - 20 m

Item no.: 10193 - 30 m

Item no.: 10195 - 50 m

RUNPOSTICKS RUNPOSTICKS

Item no.: 10020 - Comfort

Item no.: 10016 - Standard

GF4.5 to GF15 Fiberglass rod

Ø 4,5 - 6 - 7,5 - 9 - 11 - 15 m