Ground works Camlok



CP Pile pitching clamps

Working load limit (WLL) 2000 - 5000 kg

The CP pile pitching clamps are specifically designed for pitching sheet steel piling. These clamps come fitted with a 15 metre length of rope which allows the clamp to be released from the ground. The clamp comes fitted as standard with a shackle.

Product group: I2



INFO

These clamps are not designed for extracting driven piles.

Technical data CP

| Model | ArtNo. | WLL | Jaw width | Throat depth | Pin | Weight |
|-------|-------------|------|-----------|--------------|----------|--------|
| | | | | | diameter | |
| | | kg | mm | mm | mm | kg |
| CP2 | N4300000067 | 2000 | 20 | 228 | 20 | 19 |
| CP3 | N430000068 | 3000 | 26 | 228 | 30 | 22 |
| CP5 | N4300000070 | 5000 | 35 | 228 | 30 | 28 |

Dimensions CP

| Model | CP2 | CP3 | CP5 |
|-------|-----|-----|-----|
| A, mm | 90 | 100 | 115 |
| B, mm | 38 | 40 | 45 |
| C, mm | 38 | 38 | 38 |
| D, mm | 215 | 225 | 240 |
| E, mm | 114 | 124 | 139 |
| F, mm | 411 | 438 | 477 |
| G, mm | 71 | 91 | 117 |
| H, mm | 46 | 63 | 82 |
| J, mm | 19 | 25 | 32 |
| K, mm | 200 | 200 | 200 |

